

# Moon Visions R30 Uplight Bullet

## MVM-U R30 Uplight

- **Lamp Types:** R30/PAR30 lamps—Mercury Vapor (100W Max), Metal Halide (70W Max), and Incandescent (75W Max)
- **Housing (BR30):** 380 Aluminum alloy die cast housing
- **Upshield (USR30):** Die cast aluminum with convex glass lens. Sealed with 50 year-life silicon solution and high temperature silicone sponge gaskets. Positive stainless screw mount attachment.
- **Lens:** Heat resistant crystal tempered convex glass lens.
- **Knuckle:** Forward placement for better balance. Adjustable in 7.5° increments for precise aiming. 1/2" NPSM threaded arm. Knuckle may be threaded into Myer's Hubs, Tree Mounts, Surface Mounts, Ground Stakes, or Junction Boxes.
- **Finish:** Super polyester Duracoat™ powder coat with 5 year warranty. South Florida exposure rating for 5 years. Powder coated inside and outside! Standard finishes are Hartford Green (G) and Antique Bronze (B).
- **Socket:** Leviton 4KV Pulse rated 600V porcelain lampholders with 25% more lamp contact area than Chinese sockets.
- **Ballast:** Required for Mercury Vapor and Metal Halide lamps. Universal Lighting Technologies ballast housed in 6" x 7" x 4" steel box (for single ballast setups) or a 6" x 12" x 4" steel box (for double ballast setups). The ballast box is powder coated the same color as the fixture. Each MV or MH lamp requires one ballast. Please note that the wattage of the ballast **MUST** match the wattage of the lamp used.
- **Optics:** MVM bullets are available with Flood (FL) or Spot (SP) optics for use with MV or MH E17 shaped lamps and spiral fluorescents. Unless an optic is being utilized, the MVM bullet requires an R or PAR type reflector lamp.

